

USB to RAW SIR SERIAL ADAPTER

ACT-IR224UN-L210, *Compatible with Tekram IRMate IR210*

- Supports baud rates: 1.2, 2.4, 4.8, 9.6, 19.2, 38.4, 57.6, 115.2 Kbps.
- Compatible with Tekram IRMate IR210, as **one piece USB-IR adapter**.
- IR pulse: 1.63 μ S.
- No IrDA[®] protocol supported, only Raw IR (IrPHY[™] only).
- Virtual COM port supported. Nothing or minimum change in users' software, which already worked well with original Raw IR RS232 adapters.
- Less latency time, average 1.5 mS. Latency of a real COM port is 0.5 mS.
- Fully compliant with USB 3.0
- 256 bytes outbound buffer and 256 bytes inbound buffer.
- Supports Windows 2000/ XP/Vista/7/8, Mac OS, Linux and WinCE.

All trademarks, logos, company and product model names are the properties of the respective owners.



USB to RAW SIR SERIAL ADAPTER

ACT-IR224UN-L210, *Compatible with Tekram IRMate IR210*

- **Compatibility:**

Fully compliant with USB 3.0 and Raw IR

- **Communication speed and Distance:**

1200, 2400, 4800, 9600, 19200, 38400, 57600, 115200 bps; 1 cm ~158 cm

- **Power Source:**

Obtains power from USB

- **Power Consumption:**

Active current: < 60 mA, standby current: < 15 mA

- **Dimension / Weight:**

62 mm (L) X 36 mm (W) X 19 mm (H), Cable length=120 cm / 61g

- **Operating / Storage Temperature:**

0° C to +60° C / -20° C to +85° C

- **Compatible with the following Raw IR devices:**

Tekram IRMate IR210

All trademarks, logos, company and product model names are the properties of the respective owners.